



TIRES YOU CAN RELY ON

### Service guarantee

The sales service network of TIANLI extends the major provinces and cities across China and more than 100 countries worldwide. In the meantime, TIANLI provides customization and one-stop tire solutions to our customers.



- One stop supply of more than 2000 SKU+ off highway tires
- OEM fitment by many international machines
- More than 35 years experience in research and development
- Listed No. 8 in global tire manufacturer ranking

## OTR CATALOGUE

2023



گسترش تجارت تایر خاورمیانه  
MIDDLE EAST DEVELOPING  
TYRE BUSINESS



E-2 TUE100 II



- Enlarged contact area guarantees good traction.
- “All Steel Radial Construction”, optimal for high speed crane applications.
- Offers excellent on-road performance for high speed service.
- Increased durability and wear life combined with light-weight, reduced vibration and low-noise operation.
- Aggressive tread design for optimal grip and performance.



E-3 TUE300



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generates a reliable final product.
- High-tensile specialized wire.
- Optimized E3 tread pattern.
- Fine-tuned for enhanced stability, smooth running & lifetime.
- Wear, Cut & Heat resistant compounds for optimal performance.
- Suitable for Rigid Dumper applications.
- Reinforced sidewall for improved stability and protection.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
385/95R25	TL	10.00/15	E-2	170F/170G	★★★	24	1369	379	900	6000	80/90
						30	53.9	14.9	131	13200	50/54
445/95R25	TL	11.25/2.0	E-2	174F/177F	★★★	26	1481	435	900	6700/7300	80
						33	58.3	17.1	131	14800/16100	50

Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
18.00R25	TL	13.00/2.5	E-3	185B	★★	32	1623	504	700	9250	50
						40	63.9	19.8	102	20400	30



E-3+  
L-3+

## TUE301



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generates a reliable final product.
- High-tensile specialized wire.



E-3  
L-3

## TUE302



- Optimized pattern for ideal wear and low cost operation.
- Special cut-resistant and low-wear rubber compound.
- Reinforced sidewall with circumferential flank protection for effective protection against damage.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
850/65R25	TL	27.00/3.5	E-3+/L-3+	196B	★★	47	1730	830	425	12500	50
						59	68.1	32.7	62	27600	30
				217A2	★★	47	1730	830	625	23000	10
						59	68.1	32.7	91	50700	6

Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
17.5R25	TL	14.00/1.5	E-3	167B	★★	27	1340	438	525	5450	50
						34	52.8	17.2	76	12000	30
			L-3	182A2	★★	27	1340	438	650	8500	10
						34	52.8	17.2	94	18700	6
20.5R25	TL	17.00/2.0	E-3	177B	★★	33	1497	508	525	7300	50
						42	58.9	20	76	16100	30
			L-3	193A2	★★	33	1497	508	650	11500	10
						42	58.9	20	94	25400	6
23.5R25	TL	19.5/2.5	E-3	185B	★★	36	1611	588	525	9250	50
						45	63.4	23.1	76	20400	30
			L-3	201A2	★★	36	1611	588	650	14500	10
						45	63.4	23.1	94	32000	6



E-3 TUE303



- Better ground impression, optimum ground pressure distribution and low ground compaction to provide longer service time.
- Tensile-steel cord, provide higher load capacity and better fatigue resistance.
- Unique design minimizes temperature build-up and reduce deformation.
- The non-directional tread pattern for excellent traction.
- Reinforced sidewall design increase the protection and anti-puncture capability.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
14.00R24	TT					27	1367	376	800	6150	50
14.00R25	TT/TL	10.00	E-3	171B	★★★	34	53.8	14.8	116	13600	30
16.00R25	TT/TL	11.25/2.0	E-3	180B	★★★	32	1475	430	800	8000	50
						40	58.1	16.9	116	17600	30

E-3 TUE303S



- Better ground impression, optimum ground pressure distribution and low ground compaction to provide longer service time.
- Tensile-steel cord, provide higher load capacity and better fatigue resistance.
- Unique design minimizes temperature build-up and reduce deformation.
- The non-directional tread pattern for excellent traction.
- Reinforced sidewall design increase the protection and anti-puncture capability.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
16.00R25	TT/TL	11.25/2.0	E-3	180B	★★★	34	1495	430	800	8000	50
						43	58.9	16.9	116	17600	30





E-3 **TUE303 II**



- Better ground impression, optimum ground pressure distribution and low ground compaction to provide longer service time.
- Tensile-steel cord, provide higher load capacity and better fatigue resistance.
- Unique design minimizes temperature build-up and reduce deformation.
- The non-directional tread pattern for excellent traction.
- Reinforced sidewall design increase the protection and anti-puncture capability.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
14.00R25	TT/TL	10.00/2.0	E-3	169B/188A2	★★★	27	1370	375	700	5800	50/10
						34	53.9	14.8	102	12800	30/6
16.00R25	TT/TL	11.25/2.0	E-3	180B	★★★	34	1495	430	800	8000	50
						43	58.9	16.9	116	17600	30

E-3 **TUE333**



- Aggressive lug design with large blocks at tread centre provides excellent traction and braking on rough road.
- Different compounds to optimize performance in all applications.
- Additional protective sidewalls are shaped to minimize damage from cutting.
- Optimised Retreading Ability because of the robust casing.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
14.00R25	TT/TL	10.00/2.0	E-3	169B/188A2	★★★	27	1370	375	700	5800	50/10
						34	53.9	14.8	102	12800	30/6
16.00R25	TT/TL	11.25/2.0	E-3	180B	★★★	34	1495	430	800	8000	50
						43	58.9	16.9	116	17600	30



**E-3 TUE390**



- Good tread net-gross ratio provides superb traction.
- Superior compound equips tires with satisfactory manoeuvrability under extreme circumstances.
- High-tensile specialized wire.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
33.25R35	TL	27.00/3.5	E-3	212B	★★	43.4	2222	861	525	20000	50
						55	87.5	33.9	76	44100	30
37.25R35	TL	31.00/4.0	E-3	218B	★★	47.4	2389	946	525	23600	50
						60	94.1	37.2	76	52000	30

**E-4 TUE400**



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generates a reliable final product.
- High-tensile specialized wire.
- Optimized E4 tread pattern.
- Fine-tuned for enhanced stability, smooth running & lifetime.
- Wear, Cut & Heat resistant compounds for optimal performance.
- Suitable for Rigid Dumper applications.
- Reinforced sidewall for improved stability and protection.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
18.00R33	TL	13.00/2.5	E-4	191B	★★	55	1858	515	700	10900	50
				69	73.1	20.3	102	24000	30		
				55	1858	515	800	12150	50		
21.00R33	TL	15.00/3.0	E-4	200B	★★	69	73.1	20.3	116	26800	30
				55	1980	590	700	14000	50		
				69	78.0	23.2	102	30900	30		
21.00R35	TL	15.00/3.0	E-4	201B	★★	55	2032	590	700	14500	50
				69	80.0	23.2	102	32000	30		
				63	2160	653	700	18500	50		
24.00R35	TL	17.00/3.5	E-4	209B	★★	79	85.0	25.7	102	40800	30
				70	2675	738	700	27250	50		
27.00R49	TL	19.50/4.0	E-4	223B	★★	88	105.3	29.1	102	60100	30
				77	2887	825	700	33500	50		
30.00R51	TL	22.00/4.5	E-4	230B	★★	97	113.7	32.5	102	73900	30
				94.9	3047	911	700	38750	50		
33.00R51	TL	24.00/5.0	E-4	235B	★★	120	120.0	35.9	102	85500	30
				85	3190	979	700	46250	50		
36.00R51	TL	26.00/5.0	E-4	241B	★★	107	125.6	38.5	102	102000	30
				92	3384	1031	700	51500	50		
37.00R57	TL	27.00/6.0	E-4	245B	★★	116	133.2	40.6	102	113500	30
				98.1	3577	1116	700	60000	50		
40.00R57	TL	29.00/6.0	E-4	250B	★★	124	140.8	43.9	102	132500	30



**E-4 TUE400 PRO**



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generates a reliable final product.
- High-tensile specialized wire.
- Deepened E4 tread depth, effectively improve the lifetime
- Fine-tuned for enhanced stability, smooth running, and lifetime.
- Wear, Cut and Heat resistant compounds for optimal performance, suitable for different applications.
- Reinforced sidewall for improved stability and protection.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
27.00R49	TL	19.5/4.0	E-4	223B	★★	82	2691	740	700	27250	50
						103	105.9	29.1	102	60100	30

**E-4 TUE401**



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generates a reliable final product.
- High-tensile specialized wire.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
14.00R25	TT/TL	10.00	E-4	171B	★★★	38	1406	384	800	6150	50
						48	55.4	15.1	116	13600	30
16.00R25	TT/TL	11.25/2.0	E-4	180B	★★★	42	1495	438	800	8000	50
						53	58.9	17.2	116	17600	30
18.00R25	TL	13.00/2.5	E-4	185B	★★	55	1672	510	700	9250	50
						69	65.8	20.1	102	20400	30



**E-4 TUE401 II**



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generates a reliable final product.
- High-tensile specialized wire.
- Better ground impression, optimum ground pressure distribution and low ground compaction to provide longer service time.
- Steel belt construction provide 15% more load capacity compared to last generation.
- Unique design minimizes temperature build-up and reduce deformation.
- Ultra-deep block pattern provides puncture resistance and excellent traction performance. Self clean pattern to avoid damage by rock. Enhanced shoulder design for better anti-puncture performance.
- Reinforced sidewall design increase the protection and anti-puncture capability.
- Compatible with normal or heat resistance compound.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
12.00R20	TT	8.5	E-4	156/153B	★★★	33	1122	313	900	4000/3650	50
				42	44.2	12.3	131	8820/8050	30		
				162/158B	★★★	33	1122	313	930	4750/4250	50
				42	44.2	12.3	135	10500/9370	30		
12.00R24	TT/TL	8.5	E-4	160/156F	★★★	33	1226	313	850	4500/4000	80
				42	48.3	12.3	123	9920/8820	50		
				164/161B	★★★	33	1226	313	970	5000/4625	50
				42	48.3	12.3	141	11000/10200	30		
14.00R25	TT/TL	10.00/2.0	E-4	169B/188A2	★★★	38	1400	375	700	5800	50/10
						48	55.1	14.8	102	12800	30/6
16.00R25	TT/TL	11.25/2.0	E-4	180B	★★★	44	1495	430	800	8000	50
						55	58.9	16.9	116	17600	30

**E-4 TUE402**



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generate reliable final product.
- High-tensile specialized wire.
- Excellent stability and manoeuvrability.
- Special compounds deliver exceptional wear and cut resistance.
- Deep tread depth for exceptional traction and extended wear life.
- Superior flotation and rides comfort.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
24.00R35	TL	17.00/3.5	E-4	209B	★★	63	2160	663	700	18500	50
						79	85.0	26.1	102	40800	30
27.00R49	TL	19.50/4.0	E-4	223B	★★	75.5	2691	738	700	27250	50
						95	105.9	29.1	102	60100	30
33.00R51	TL	24.00/5.0	E-4	235B	★★	95	3032	945	700	38750	50
						120	119.4	37.2	102	85500	30





**E-4 TUE402 PRO**



- Aggressive lug design with large blocks at tread centre provides excellent traction and braking on rough road.
- Different compounds to optimize performance in all applications.
- Additional protective sidewalls are shaped to minimize damage from cutting.
- Optimised Retreading Ability because of the robust casing.



**E-4 TUE406**



- Unique tread pattern design equips tire with excellent traction.
- Special curing procedures generates a reliable final product.
- High-tensile specialized wire.
- Equipped with excellent stability and flexibility.
- Special cut-resistant and low-wear rubber compound.
- Ultra-deep pattern provides excellent traction and wear resistance performance.
- Superior flotation and rides comfort.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
18.00R25	TL	13.00/2.5	E-4	185B	★★	51	1673	498	700	9250	50
						64	65.9	19.6	102	20400	30
18.00R33	TL	13.00/2.5	E-4	189B	★★★	51	1673	498	800	10300	50
						64	65.9	19.6	116	22700	30
18.00R33	TL	13.00/2.5	E-4	195B	★★★	54	1875	500	800	12150	50
						68	73.8	19.7	116	26800	30
21.00R33	TL	15.00/3.0	E-4	203B	★★★	54	1955	570	800	15500	50
						68	77	22.4	116	34200	30
21.00R35	TL	15.00/3.0	E-4	204B	★★★	61	2050	570	800	16000	50
						77	80.7	22.4	116	35300	30
24.00R35	TL	17.00/3.5	E-4	212B	★★★	65	2175	655	800	20000	50
						82	85.6	25.8	116	44100	30

Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
27.00R49	TL	19.5/4.0	E-4	223B	★★	72	2700	735	700	27250	50
						91	106.3	28.9	102	60100	30



E-4 **TUE410**



- Reinforced carcass design guarantees longer tire service time.
- High-tensile specialized wire to guarantee tire safety and service life in harsh working condition.
- Unique tread pattern design equips tire with excellent traction.
- Optimized E4 tread pattern.
- Fine-tuned for enhanced stability, traction, footprint, life time and smooth running.
- Wear, Cut and Heat resistant compounds for optimal performance.
- Suitable for Dumper applications.
- Reinforced sidewall for improved stability and protection.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
46/90R57	TL	32.00/6.0	E-4	252B	★★	98	3570	1180	700	63000	50
						123	140.6	46.5	102	139000	30
50/80R57	TL	34.00/5.0	E-4	257B	★★	98	3556	1270	700	73000	50
						123	140.0	50.0	102	161000	30
59/80R63	TL	44.00/5.0	E-4	268B	★★	116	4011	1534	800	100000	50
						146	157.9	60.4	116	220500	30

E-4 **TUE555**



- Better ground impression, optimum ground pressure distribution and low ground compaction to provide longer service time.
- Tensile-steel cord, provide higher load capacity and better fatigue resistance.
- Unique design minimizes temperature build-up and reduce deformation.
- The non-directional tread pattern for excellent traction.
- Reinforced sidewall design increase the protection and anti-puncture capability.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
16.00R25	TT/TL	11.25/2.0	E-4	180B	★★★★	46	1495	430	800	8000	50
						58	58.9	16.9	116	17600	30



**E-3 TUE666**



- Better ground impression, optimum ground pressure distribution and low ground compaction to provide longer service time.
- Tensile-steel cord, provide higher load capacity and better fatigue resistance.
- Unique design minimizes temperature build-up and reduce deformation.
- The non-directional tread pattern for excellent traction.
- Reinforced sidewall design increase the protection and anti-puncture capability.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
16.00R25	TT/TL	11.25/2.0	E-3	180B	★★★	29	1495	430	800	8000	50
						37	58.9	16.9	116	17600	30

**E-3/L-3 IND-3 TUL300**



- Optimum distribution of tread blocks for ride comfort and traction on loose ground.
- Special cut-resistant and low-wear rubber compound.
- Reinforced sidewall with circumferential flank protection for effective protection against damage.
- Classic E3/L3 tread pattern.
- Fine tuned for enhanced stability, lifetime, smooth running.
- Wear and Cut resistant compounds.
- Suitable for Loader and dumper applications.
- Reinforced scuff bands for improved sidewall protection.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
15.5R25	TL	12.00/1.3	E-3/L-3	152B	★	24.4	1275	405	375	3550	50
						31	50.2	15.9	54	7830	30
						24.4	1275	405	500	5900	10
17.5R25	TL	14.00/1.5	E-3/L-3	167B	★★	31	50.2	15.9	73	12800	6
						27	1347	449	525	5450	50
						34	53.0	17.7	76	12000	30
20.5R25	TL	17.00/2.0	E-3/L-3	182A2	★★	27	1347	449	650	8500	10
						34	53.0	17.7	94	18700	6
						31	1482	533	525	7300	50
23.5R25	TL	19.5/2.5	E-3/L-3	177B	★★	39	58.3	21.0	76	16100	30
						31	1482	533	650	11500	10
						39	58.3	21.0	94	25400	6
26.5R25	TL	22.00/3.0	IND-3	193A2	★★★	31	1482	533	800	13200	10
						39	58.3	21.0	116	29100	6
						41	1602	607	525	9250	50
29.5R25	TL	25.00/3.5	E-3/L-3	185B	★★	52	63.1	23.9	76	20400	30
						41	1602	607	650	14500	10
						52	63.1	23.9	94	32000	6
15.5R25	TL	12.00/1.3	IND-3	201A2	★★	41	1602	607	800	17000	10
						52	63.1	23.9	116	37500	6
						38	1735	686	525	11500	50
17.5R25	TL	14.00/1.5	E-3/L-3	206A2	★★★	48	68.3	27.0	76	25400	30
						38	1735	686	650	18500	10
						48	68.3	27.0	94	40800	6
20.5R25	TL	17.00/2.0	IND-3	214A2	★★★	38	1735	686	800	21200	10
						48	68.3	27.0	116	46700	6
						45	1860	769	525	14000	50
23.5R25	TL	19.5/2.5	E-3/L-3	200B	★★	57	73.2	30.3	76	30900	30
						45	1860	769	650	22400	10
						57	73.2	30.3	94	49400	6



E-3/L-3  
IND-3

## TUL302



- Optimized pattern for ideal wear and low cost operation.
- Special cut-resistant and low-wear rubber compound.
- Reinforced sidewall with circumferential flank protection for effective protection against damage.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
17.5R25	TL	14.00/1.5	E-3/L-3	167B	★★	26	1345	452	525	5450	50
				182A2	★★	33	53.0	17.8	76	12000	30
						26	1345	452	650	8500	10
20.5R25	TL	17.00/2.0	E-3/L-3	177B	★★	33	53.0	17.8	94	18700	6
						31	1480	540	525	7300	50
						39	58.3	21.3	76	16100	30
						31	1480	540	650	11500	10
						39	58.3	21.3	94	25400	6
23.5R25	TL	19.5/2.5	E-3/L-3	185B	★★	31	1480	540	800	13200	10
						39	58.3	21.3	116	29100	6
						34	1610	605	525	9250	50
						43	63.4	23.8	76	20400	30
						34	1610	605	650	14500	10
26.5R25	TL	22.00/3.0	IND-3	201A2	★★	43	63.4	23.8	94	32000	6
						34	1610	605	800	17000	10
						43	63.4	23.8	116	37500	6
						36	1735	686	525	11500	50
						45	68.3	27.0	76	25400	30
29.5R25	TL	25.00/3.5	E-3/L-3	193B	★★	36	1735	686	650	18500	10
						45	68.3	27.0	94	40800	6
						36	1735	686	800	21200	10
						45	68.3	27.0	116	46700	6
						43	1857	750	525	14000	50
29.5R25	TL	25.00/3.5	E-3/L-3	200B	★★	54	73.8	29.5	76	30900	30
						43	1857	750	650	22400	10
						54	73.8	29.5	94	49400	6

E-4  
L-4

## TUL400



- Optimized pattern for ideal wear and low cost operation.
- Special cut-resistant and low-wear rubber compound.
- Reinforced sidewall with circumferential flank protection for effective protection against damage.
- Optimized E4/L4 tread pattern.
- Fine-tuned for enhanced stability, traction, footprint, life time and smooth running.
- Wear, Cut and Heat resistant compounds for optimal performance.
- Suitable for Loader & Dumper applications.
- Reinforced sidewall for improved stability and protection.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)		
23.5R25	TL	19.5/2.5	E-4/L-4	185B	★★	55	1660	600	525	9250	50		
						69	65.4	23.6	76	20400	30		
						201A2	★★	55	1660	600	650	14500	10
26.5R25	TL	22.00/3.0	E-4/L-4			69	65.4	23.6	94	32000	6		
						55	1788	685	525	11500	50		
						69	70.4	27.0	76	25400	30		
						193B	★★	55	1788	685	650	18500	10
						209A2	★★	69	70.4	27.0	94	40800	6
29.5R25	TL	25.00/3.5	E-4/L-4	200B	★★	57.5	1906	760	525	14000	50		
						72	75.0	29.9	76	30900	30		
						216A2	★★	57.5	1906	760	650	22400	10
				72	75.0	29.9	94	49400	6				





L-5 **TUL500**



- Optimized pattern for ideal wear and low cost operation.
- Special cut-resistant and low-wear rubber compound.
- Reinforced sidewall with circumferential flank protection for effective protection against damage.
- Classic L5 tread pattern.
- Fine-tuned for enhanced stability, traction, life time and smooth running.
- Wear, Cut and Heat resistant compounds for optimal performance.
- Suitable for extreme conditions.
- Reinforced sidewall for improved stability and protection.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
20.5R25	TL	17.00/2.0	L-5	193A2	★★	71	1545	534	650	11500	10
						89	60.8	21.0	94	25400	6
23.5R25	TL	19.5/2.5	L-5	201A2	★★	80	1672	604	650	14500	10
						101	65.8	23.8	94	32000	6
26.5R25	TL	22.00/3.0	L-5	209A2	★★	97.5	1760	690	650	18500	10
						123	69.3	27.2	94	40800	6
35/65R33	TL	28.00/3.5	L-5	224A2	★★	97	2038	864	650	28000	10
						122	80.2	34.0	94	61700	6

L-5 **TUL505**



- Super deep tread pattern designed for wheel loader, dozer and grader requiring maximum traction.
- Perfect lug face ensures equal load distribution and even contact area.
- Additional protective sidewalls are shaped to minimize damage from cutting.
- Optimised Retreading Ability because of the robust casing.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
23.5R25	TT/TL	19.50/2.5	L-5	201A2	★★	76	1675	595	650	14500	10
						96	65.9	23.4	94	32000	6
26.5R25	TT/TL	22.00/3.0	L-5	209A2	★★	86	1800	675	650	18500	10
						108	70.9	26.6	94	40800	6
29.5R25	TT/TL	25.00/3.5	L-5	216A2	★★	94	1920	750	650	22400	10
						118	75.6	29.5	94	49400	6



L-5S TUL580



- Optimized pattern for ideal wear and low cost operation.
- Special cut-resistant and low-wear rubber compound.
- Reinforced sidewall with circumferential flank protection for effective protection against damage.
- Classic L5S Smooth tread pattern.
- Fine-tuned for enhanced stability, traction, life time and smooth running.
- Wear, Cut and Heat resistant compounds for optimal performance.
- Suitable for extreme conditions.
- Reinforced sidewall for improved stability and protection.



L-5S TUL580 PRO



- Smooth extra deep tread tyres designed for all kinds of operations on severe rocky surface.
- Enforced sidewall protection rib help reduce all kinds of damage to sidewall.
- Cut resistance compound ensures a maximum resistance to cut & wearing.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
12.00R24	TT	8.5	L-5S	175A2	★★	55	1277	328	800	6900	10
						69	50.3	12.9	116	15200	6
14.00R24	TT	10.00	L-5S	186A2	★★	63.5	1418	372	800	9500	10
						80	55.8	14.6	116	20900	6
17.5R25	TL	14.00/1.5	L-5S	182A2	★★	65	1398	442	650	8500	10
						82	55.0	17.4	94	18700	6
18.00R25	TL	13.00/2.5	L-5S	204A2	★★	82	1677	506	825	16000	10
						103	66.0	19.9	120	35300	6
26.5R25	TL	22.00/3.0	L-5S	209A2	★★	97.5	1760	690	650	18500	10
						123	69.3	27.2	94	40800	6
29.5R25	TL	25.00/3.5	L-5S	216A2	★★	97	1906	770	650	22400	10
						122	75.0	30.3	94	49400	6
35/65R33	TL	28.00/3.5	L-5S	224A2	★★	97	2085	873	650	28000	10
						122	82.1	34.4	94	61700	6

Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
10.00R20	TT/TL	7.5	L-5S	166A2	★★	37	1052	275	950	5300	10
						47	41.4	10.8	138	11700	6
12.00R20	TT/TL	8.5	L-5S	175A2	★★	48	1122	313	950	6900	10
						60	44.2	12.3	138	15200	6
17.5R25	TT/TL	14.00/1.5	L-5S	182A2	★★	66	1400	445	650	8500	10
						83	55.1	17.5	94	18700	6
18.00R25	TT/TL	13.00/2.5	L-5S	206A2	★★★	82	1675	500	900	17000	10
						103	65.9	19.7	131	37500	6
26.5R25	TL	22.00/3.0	L-5S	209A2	★★	94	1800	660	650	18500	10
						118	70.9	26.0	94	40800	6
29.5R29	TL	25.00/3.5	L-5S	218A2	★★	100	2025	750	650	23600	10
						126	79.7	29.5	94	52000	6



## TUP420



- New generation radial heavy forklift tyres.
- Robust sidewall guarantee great low deflection rate.
- Cool running compound offer low heat build up in operation.

Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
12.00R24	TT/TL	8.5	-	178A5	-	40	1418	375	1000	7500	25
						50	55.8	14.8	145	16500	15
14.00R24	TT/TL	10.00/2.0	-	193A5	-	64	1418	375	1000	11500	25
						81	55.8	14.8	145	25400	15

## E-3 L-3 TU201



- Light duty snow pattern designed for muddy and snow application.
- Special traction resistance compound.
- Strong sidewalls are shaped to minimize the damage from cutting.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
17.5R25	TL	14.00/1.5	E-3/L-3	167B/182A2	★★	25	1330	424	525/650	5450/8500	50/10
						31	52.4	16.7	76/94	12000/18700	30/6
20.5R25	TL	17.00/2.0	E-3/L-3	177B/193A2	★★	28	1480	496	525/650	7300/11500	50/10
						35	58.3	19.5	76/94	16100/25400	30/6
23.5R25	TL	19.5/2.5	E-3/L-3	185B/201A2	★★	31	1600	574	525/650	9250/14500	50/10
						39	63.0	22.6	76/94	20400/32000	30/6



E-3/L-3  
G-2

## TU202



- Open tread pattern in shoulder ensure good self-cleaning in the snow and mud.
- Unique winter compound ensure excellent traction in mud and on snow and ice.
- New designed side-wall with a protective band on the shoulder/sidewall interface provides good protection against accidental damage.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
340/80R18	TL	11.00	-	143A8/136B	-	20	1001	343	375	2725/2240	40/50
						25	39.4	13.5	54	6005/4940	24/30
335/80R20	TL	9.00	-	147A2/136B	-	20	1044	333	375	3075/2240	10/50
						25	41.1	13.1	54	6780/4940	6/30
405/70R20	TL	13.00	-	155A2/143B	-	25	1076	407	375	3875/2725	10/50
						31	42.4	16.0	54	8540/6005	6/30
405/70R24	TL	13.00	-	158A2/146B	-	24	1178	407	375	4250/3000	10/50
						30	46.4	16.0	54	9370/6610	6/30
14.00R24	TL	8.00TG	G-2	155A8	★★	25	1350	360	450	3875	40
						31	53.1	14.2	65	8540	24
15.5R25	TL	12.00/1.3	E-3/L-3	160B/176A2	★★	25	1275	395	525/650	4500/7100	50/10
						31	50.2	15.6	76/94	9920/15700	30/6
17.5R25	TL	14.00/1.5	E-3/L-3	167B/182A2	★★	28	1350	445	525/650	5450/8500	50/10
						35	53.1	17.5	76/94	12000/18700	30/6
20.5R25	TL	17.00/2.0	E-3/L-3	177B/193A2	★★	31	1490	520	525/650	7300/11500	50/10
						39	58.7	20.5	76/94	16100/25400	30/6
23.5R25	TL	19.5/2.5	E-3/L-3	185B/201A2	★★	34	1615	595	525/650	9250/14500	50/10
						43	63.6	23.4	76/94	20400/32000	30/6
650/65R25	TL	19.5/2.5	E-3/L-3	180B/200A2	★★	38	1480	640	425/625	8000/14000	50/10
						48	58.3	25.2	62/91	17600/30900	30/6
750/65R25	TL	24.00/3.0	E-3/L-3	190B/209A2	★★	43	1610	755	425/625	10600/18500	50/10
						54	63.4	29.7	62/91	23400/40800	30/6

E-3

## TU306



- The non-directional E-3 tire for articulated dump truck.
- Cut resistant tread design for even wear.
- Built-up sidewall for protection against sidewall penetrations.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
33.25R29	TL	27.00/3.5	E-3	209B	★★	50	2090	845	525	18500	50
						63	82.3	33.3	76	40800	30
800/80R29	TL	27.00/3.5	E-3	209B	★★	50	2090	845	525	18500	50
						63	82.3	33.3	76	40800	30





## R307



- Small diamond-shaped pattern ensures the driving performance.
- The super wide contact area provides enough flotation and avoids sinking.
- The arc-shaped outline ensures the driving flexible performance in the sand.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
24R20.5	TL	18.00	E-7	176F	-	18	1370	594	600	7100	80
						23	53.9	23.4	87	15700	48



## R308



- The blocky tread pattern used for sand and highway is suitable for driving in harsh working condition.
- To lower the pressure in the sand provides good flotation and driving performance.
- The standard pressure on the highway provides excellent driving controllability.
- It's suitable for long distance and high speed transportation.



Size	TT/TL	Rim	TRA Code	Load Speed Index	Star Rating	Tread Depth (mm/32ND)	Overall Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (KPA/PSI)	Loading Capacity (Kg/Lbs)	Speed (Km/mph)
16.00R20	TL	10.00W	-	174/171G	-	28	1325	408	760	6700/6150	90
						35	52.2	16.1	110	14800/13600	54